# **Excel-Crete Tinted Additive**

**Data Sheet** 

## Tinted Additive for Excel-Crete K/D and K/D II Applications

#### **COMPOSITION:**

Excel-Crete Tinted Additive is a single-component, acrylic additive for use with the Excel-Crete K/D powder.

#### **BASIC USE:**

Excel-Crete Tinted Additive is mixed with the Excel-Crete K/ D powder to provide a pigmented polymer modified cement. The mixed cement product is used to provide a texture or pattern coat over Excel-Coat waterproof deck coating systems or on-grade as a decorative finish.

## LIMITATIONS:

- Not for areas intended for vehicular traffic.
- Do not apply in constantly submerged conditions such as reflecting ponds or tank linings.
- Do not apply directly to plywood. For plywood applications refer to the *Excel-Coat Fire System Application Guide*.
- On-grade applications require appropriate surface preparation and prime coat.

#### **GRADE:**

The Excel-Crete Tinted Additive is a liquid component that is added to the Excel -Crete K/D powder. Upon mixing of the two components the pigmented material may be sprayed or trowel applied to provide a decorative texture or finish pattern.

#### PACKAGING:

The Excel-Crete Tinted is available in 1 and 5 gallon containers (U.S. gallon measures).

#### SHELF LIFE:

Twelve months from shipping date stored below 80°. Do not allow product to freeze.

#### COLORS:

Excel-Crete Tinted Additive is available in 20 standard colors. Custom color matching is available upon request at an additional charge. Minimum quantities and guaranteed overages may apply.

#### JOB CONDITIONS:

Before any work is started, the applicator shall thoroughly examine all surfaces for any deficiencies. Should any deficiencies exist, the Architect, Owner or General Contractor shall be notified in writing and any corrections necessary shall be made.

Cold or inclement weather will affect the cure time of all Excel-Coat products. Do not install over wet substrate, in the rain or, if the threat of rain exists within 24 hours.

#### **INSTALLATION:**

Refer to the appropriate *Excel-Coat K/D or K/D II Application Guide* for installation instructions.

#### **STORAGE AND HANDLING:**

Store Excel-Coat products in a cool, dry area and protect from freezing. It will be necessary to stir Excel-Crete Tinted Additive before using. Partial containers can be resealed.

# **Excellent Coatings International**

10880 Poplar Avenue, Fontana, CA 92337 909-823-8800 800-473-3817 Fax: 909-823-6309 http://excellentcoatings.com Email: info@excellentcoatings.com

Should a top skin develop on the remaining contents of a container, the physical properties and effectiveness of the contents will not be impaired. Clean mixing and application tools with water. Dispose of empty containers properly according to current Local, State and Federal regulations.

### HEALTH AND HAZARD INFORMATION:

Use the product with adequate ventilation and personal protection. Users must read container label and Safety Data Sheet (SDS) for specific health and safety precautions prior to use.

#### AVAILABILITY:

Immediately available from Excellent Coatings International and authorized distributors.

#### COST:

Cost data is available from your local Excellent Coatings International authorized representative. For the name and number of the nearest local representative, call Excellent Coatings International at (800) 473-3817.

#### **MAINTENANCE:**

Cleaning can be accomplished by scrubbing with detergent soap and water. Heavy stains may require TSP solution or Excel-Coat Maintenance Cleaner and brushing with a stiff broom. Follow All Purpose Cleaner product instructions.

#### **GUARANTEE / WARRANTY:**

Excellent Coatings International warrants Excel-Coat products to be free of defects and manufactured to meet published physical properties for a period of one year following the date of shipment, provided that the product has been applied according to the manufacturer's instructions. Under this warranty, Excellent Coatings International will provide, at no charge, product in containers to replace any product proved to be defective in applications recommended by us as suitable for this product. All claims concerning the products' defects must be made within twelve months of shipment and within thirty days of discovery. Absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product. This warranty is IN LIEU OF any and all other warranties, expressed or implied, including, but not limited to, any implied warranty of MERCHANTABILITY of fitness for a specific purpose.

#### **TECHNICAL SERVICE:**

Authorized local representatives are available to provide design assistance and on-site instruction for our products. Excellent Coatings International provides assistance in design and development of special applications and partial inspection. Part-time and full-time inspection and instruction are available on a fee basis upon arrangement. Technical data is available upon request.